

KABRIC

DETALE CPH is a line of exclusive decorative products to take care of the small details. Paints and finishes are inspired by our Nordic design heritage and the changeability of nature. The products are suitable for professional as well as do-it-yourself use.



Product properties

Ultramatt, decorative paint for walls, ceilings and furniture. Produces a surface with a vibrant, textured finish. Recommended for surfaces with normal functional requirements that are exposed to moderate dirt and wear and tear. Better dirt-resistant properties and improved durability are the result when using DETALE Topcoat. Furniture should also be finished with a suitable varnish.

- Easy application
- Matt, textured finish
- Durability corresponding to flat (matt) painted surface

Labelling



Product use

Living rooms, entrances, offices, business premises, clinics, shops, hotels and restaurants. Concrete, light concrete, plaster, brick, gypsum board and previously painted surfaces.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning, sanding and dusting.
Remove dirt, grime, grease and flaking material by cleaning thoroughly.
Hard, smooth substrates should be sanded to a matt finish and painted with primer.
Cracks, unevenness and holes must be filled.
Absorbent and porous substrates can be primed with a basic primer.
Apply 2 times. Intermediate sanding of transitions and edges before final application.
Finish if needed using DETALE Topcoat.

Application

Apply using a roller, asymmetrically, evenly and in ample quantity.

Work the surface using a spatula or brush.

Decide your choice of tools based on the size of the surface finish requirements.

Apply wet on wet, minimise visible stains and transitions.

Cold/heat can affect the viscosity of the material.

Avoid condensation formation.

Cold and increased humidity extends drying time, full curing and recoating interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always test for control and acceptance of adhesion and result.

Expected result

Flat, textured surface.

Withstands cleaning with a mild cleaning agent without abrasive material, water and drying with a moist cloth.

Avoid placing loads on the surface before the treatment is fully cured.

Useful Information

The effect is produced from the way it is rolled and filled.

Be sure to apply filler in soft arches and avoid applying in the same direction.

When applied with a brush the effect that emerges is from the way the wall is made.

We recommend brushing in soft, curved motions or in short, cross strokes.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage: Cool, frost free and tightly closed

Protection equipment: Protect skin and eyes from splashes with suitable clothing, gloves and glasses. Avoid inhalation of spray mist and grinding dust. Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Product Type	Plaster & Sealant
Gloss	Ultra Matte
Density (kgs/l)	1.19
Solids Weight %	64
Solids Vol. %	57
Long spreading rate (m²/l.)	1
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	3
Fully cured at 20° C, 60 % RH (Days)	28
Cleaning of Tools etc.	Water

Current TDS Version

July 2024

Replaces TDS Version

October 2023